

GENERAL TIRE

2019 ARCA TIRE SPECIFICATIONS

Speedways (12.0/28.0R15)

	LS	RS		LS	RS
Charlotte	7416	8604	Chicago	7511	8604
Circumference	87 1/4"	88 5/8"	Circumference	87 1/4"	88 5/8"
Air Pressure	LF 28/43#	RF 56/71#	Air Pressure	LF 28/43#	RF 50/65#
Outer/Inner	LR 29/44#	RR 54/69#	Outer/Inner	LR 28/43#	RR 47/62#
Daytona	7331	8492	Gateway	7193	8278
Circumference	87 3/4"	88 1/4"	Circumference	87 1/4"	88 5/8"
Air Pressure	LF 35/50#	RF 55/70#	Air Pressure	LF 18/33#	RF 33/48#
Outer/Inner	LR 35/50#	RR 50/65#	Outer/Inner	LR 18/33#	RR 31/46#
Iowa	7193	8278	Kansas	7511	8604
Circumference	87 1/4"	88 5/8"	Circumference	87 1/4"	88 5/8"
Air Pressure	LF 20/35#	RF 36/51#	Air Pressure	LF 30/45#	RF 52/67#
Outer/Inner	LR 20/35#	RR 34/49#	Outer/Inner	LR 30/45#	RR 50/65#
Michigan	7511	8604	Pocono	7193	8278
Circumference	87 1/4"	88 5/8"	Circumference	87 1/4"	88 5/8"
Air Pressure	LF 28/43#	RF 54/69#	Air Pressure	LF 23/38#	RF 38/53#
Outer/Inner	LR 28/43#	RR 50/65#	Outer/Inner	LR 23/38#	RR 36/51#
Talladega	7331	8492			
Circumference	87 3/4"	88 1/4"			
Air Pressure	LF 35/50#	RF 55/70#			
Outer/Inner	LR 35/50#	RR 50/65#			

Inner Liner cold inflation should be at least 15 PSI above the cold tire inflation.

Short Tracks	11.0/28R15 Radials	No Inner Liners Used at Short Tracks
Elko	LF 16# RF 32#	Fairgrounds
27L/44R	LR 16# RR 30#	27L/44R
Five Flags	LF #16 RF #28	LOR
27L/44R	LR #16 RR #28	27L/44R
Madison	LF 18# RF 34#	Salem
27L/44R	LR 18# RR 32#	27L/44R
Toledo	LF 18# RF 33#	
27L/44R	LR 18# RR 31#	
Dirt Tracks	(11.0/88-15) Bias Tires	(11.0/88-15) Bias Tires
DuQuoin	LF 18# RF 24#	Springfield
45L/70R Dirts	LR 16# RR 24#	45L/70R Dirts
		LF 18# RF 22#
		LR 18# RR 22#

Nitrogen replacement procedure:

- (1) Deflate outer chamber completely.
- (2) Reduce inner chamber to **no less than 15#**
- (3) Inflate inner to recommended pressure.
- (4) Inflate outer to recommended pressure.

All Pressures are COLD Starting Recommended.

All Subject to Change. Check with General at each Event.

Rev 6/5/19