

[S-00 FRONT]



[S-00 BACK]



A lot of professionals genuinely love their subwoofer to bits. Or they hate it with every ounce of venomous foam bubbling from their mouths. We find this interesting because we know for a fact that a good share of the latter use an NHT S-00. And know none of the former. This does not surprise us. That it carries a girl name has apparently not worked against the S-00 (aka “Sue”) or its 125 watts of poop. Works like butter with the M-00 mini monitors (named, incidentally, after a cow). Footswitch jack allows sub bypass/full range monitor signal with latching type switch on the fly.



[SPECIFICATIONS]

System Type:	Integrated, self-powered, subwoofer
Configuration:	Acoustic Suspension Subwoofer
Woofers:	Long-throw 8" treated paper woofer
Magnetic Shielding:	None
Amplifier Power:	125W (continuous rms/ch), 250W (500ms peak)
Peak Acoustic Output @1M:	108dB SPL @ 60Hz
Crossover Frequency:	70Hz - 110Hz LP, 95 or 120Hz HP
Crossover Slopes:	12dB LP, 6dB HP
Frequency Response:	41Hz - 110Hz @1M +/- 3dB
-6dB Cutoff:	35Hz
Input Connectors:	XLR, TRS, RCA
Output Connectors:	TRS for channel 1 and 2, TRS for on/bypass, footswitch (not supplied)
Input Sensitivity:	-10dB or +4dB
Dimensions/Weight:	13.25" h x 10.25" w x 13" d / 30 lbs
Subwoofer Material:	MDF with black powdercoat
Controls:	On, Auto on, Off, Variable LP filter, 2 position HP filter
Subwoofer Level Indicators:	Power, Standby

